

High Bay Fixtures



Product Model	LA(I)-(BGK100W-B)	LA(I)-(BGK120W-B)	LA(I)-(BGK150W-B)	LA(I)-(BGK200W-B)
Input Power (Wattage)	100	120	150	200
Delivered Light Output (Lm)	9000	10800	13500	18000
Efficacy (Lm/W)	>90	>90	>90	>90
Color Rendering Index (CRI)	75	75	75	75
Color Temperature (K)	3000±100	3000±100	3000±100	3000±100
	4800±150	4800±150	4800±150	4800±150
	6000±300	6000±300	6000±300	6000±300
Dimmer Controls				
Dimming Compatible	PWM	PWM	PWM	PWM
Life Expectancy				
MTBF(Hours)	40,000	40,000	40,000	40,000
L70 Life (Hours)	100,000	100,000	100,000	100,000
Warranty(Years)	5	5	5	5
Physical				
Dimensions(mm)	Φ540×480	Φ540×530	Φ540×530	Φ540×762
Weight (Kg)	4.5	5.4	5.4	8.1
Number of Chips(Pcs)	3	3	3	3
Electrical				
Input Voltage Range (V/AC)	100-277	100-277	100-277	100-277
OP. Frequency (Hz)	50-60	50-60	50-60	50-60
Power Factor	>0.9	>0.9	>0.9	>0.9