

LA(O)-(570TG) FLOOD LIGHT 100W/120W/140W/160W



Product Model	LA(O)- (570TG100W)	LA(O)- (570TG120W)	LA(O)- (570TG140W)	LA(O)- (570TG160W)
Input Power (Wattage)	100	120	140	160
Delivered Light Output (Lm)	9000	10800	12600	14400
Efficacy (Lm/W)	>90	>90	>90	>90
Color Rendering Index (CRI)	75	75	75	75
Color Temperature (K)	3000±100	3000±100	3000±100	3000±100
	4800±150	4800±150	4800±150	4800±150
	6000±300	6000±300	6000±300	6000±300
Dimmer Controls				
Dimming Compatible	PWM	PWM	PWM	PWM
Life Expectancy				
MTBF(Hours)	40,000	40,000	40,000	40,000
L70 Life (Hours)	100,000	100,000	100,000	100,000
Warranty(Years)	5	5	5	5
Physical				
Dimensions(mm)	600x285x100	600x285x100	600x285x100	600x285x100
Weight (Kg)	8.5	8.5	8.5	8.5
Number of Chips(Pcs)	2	2	2	2
Electrical				
Input Voltage Range (V/AC)	85-265	85-265	85-265	85-265
OP. Frequency (Hz)	50-60	50-60	50-60	50-60
Power Factor	>0.9	>0.9	>0.9	>0.9

LIGHTING AUTOMATION

Lighting Retrofit • Lighting Automation • Energy Management • Security Solutions